

Detailed flow rates for: roof drain type 62 H PVC, heated, DN 70

Part number: 623140
GTIN: 4001636623140
Rebate group: 10

Flow rates tested to DIN EN 1253:

Nominal diameter	Description	Outlet direction	Min. flow rate according to norm	Water level according to norm	Flow rate at water level 5 mm	Flow rate at water level 15 mm	Flow rate at water level 25 mm	Flow rate at water level 35 mm	Flow rate at water level 45 mm	Flow rate at water level 55 mm	Flow rate at water level 65 mm
DN 70	With overflow adaptor 671394, free drainage (gargoyle)	vertical	1.70 l/s	35.00 mm	0.90 l/s	3.20 l/s	5.40 l/s	5.40 l/s	5.50 l/s	5.60 l/s	5.70 l/s
DN 70	With overflow adaptor 671394, with connected downpipe = 3 m, free drainage	vertical	1.70 l/s	35.00 mm	0.80 l/s	3.60 l/s	5.90 l/s	8.70 l/s	12.10 l/s	14.80 l/s	15.00 l/s
DN 70	Measurement to DIN EN 1253	vertical	1.70 l/s	35.00 mm	0.55 l/s	2.30 l/s	4.50 l/s	7.40 l/s	10.60 l/s	12.85 l/s	16.30 l/s